



Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid

Product Code

Prefix 24

Synonyms

None.

Product Use

Lubricating oils. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

None known.

FOR PRODUCT MANUFACTURED IN THE U.S.A.:

MANUFACTURER

Safety-Kleen Systems, Inc.
42 Longwater Drive
Norwell, MA 02061-9149
U.S.A.

SUPPLIER (in Canada)

Safety-Kleen Canada, Inc.
25 Regan Road
Brampton, Ontario, Canada L7A 1B2

FOR PRODUCT MANUFACTURED IN CANADA:

MANUFACTURER

Safety-Kleen Canada, Inc.
25 Regan Road
Brampton, Ontario, Canada L1A 1B2

SUPPLIER (in the U.S.A.)

Safety-Kleen Systems, Inc.
42 Longwater Drive
Norwell, MA 02061-9149
U.S.A.

www.safety-kleen.com

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

Issue Date

December 18, 2018

Supersedes Issue Date

October 9, 2017

Original Issue Date

October 9, 2017

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

Acute Toxicity - Inhalation - Vapor - Category 3

Carcinogenicity - Category 1A

GHS Label Elements

Symbol(s)



Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

Signal Word

Danger

Hazard Statement(s)

Toxic if inhaled.

May cause cancer.

Precautionary Statement(s)

Prevention

Read label before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Response

IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) Not Otherwise Classified

Repeated exposure may cause skin dryness or cracking.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-55-8	Distillates, petroleum, hydrotreated light paraffinic	28-49
64742-65-0	Petroleum distillates, solvent dewaxed heavy paraffinic	28-49
44742-58-1	PROPRIETARY ADDITIVES	2-4
64741-88-4	PROPRIETARY ADDITIVES	2-4
64762-65-0	PROPRIETARY ADDITIVES	2-4
68511-50-2	PROPRIETARY ADDITIVES	2-4

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor.

Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention, if needed.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth.

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

Most Important Symptoms/Effects

Acute

Toxic if inhaled.

Delayed

May cause cancer.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, water fog. Water or foam may cause frothing.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Dense black smoke occurs during fire.

Hazardous Combustion Products

Burning may produce oxides of carbon and unidentified organic compounds, hydrogen sulfide, alkyl mercaptan.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Keep unnecessary people away, isolate hazard area, and deny entry.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Avoid breathing vapor. Avoid contact with skin, eyes and clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal. There may be specific regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with: Skin, eyes, clothing, shoes. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Read label before use. Do not handle until all safety precautions have been read and understood. Use Personal Protective equipment as required.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up.

Keep container tightly closed and properly labeled. Store in a cool, dry, well-ventilated area. Store away from heat and direct sunlight. Avoid contact with strong oxidizers. Keep container sealed when not in use.

Keep container sealed when not in use. Store and handle in accordance with all current regulations and standards. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Empty product containers may retain product residue and can be dangerous.

Incompatible Materials

Avoid oxidizing agents and/or acids.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada, ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

Glove Recommendations

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended. When products are heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, lab coat or apron.

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear amber liquid	Physical State	Liquid
Odor	Mild petroleum ,hydrocarbon odor	Color	Amber
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	260 °C
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Negligible.	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	250 °C (482 °F)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Negligible
Vapor Density (air=1)	>1	Specific Gravity (water=1)	0.848
Water Solubility	Negligible	Partition coefficient: n-octanol/water	Not available
Viscosity	18.92 cSt 100 °C (212 °F)	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	7.075 lb/gal
VOC	42.571 %	Molecular Weight	Not available
Percent Solids	57.429 %		

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid flames, sparks and other sources of ignition. Avoid direct sunlight. Keep away from high temperatures and incompatible materials.

Incompatible Materials

Avoid oxidizing agents and/or acids.

Hazardous decomposition products

Hydrogen sulfide, alkyl mercaptan.

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

Toxic if inhaled.

Skin Contact

Repeated exposure may cause skin dryness or cracking.

Eye Contact

May cause eye irritation.

Ingestion

May cause, gastrointestinal irritation, nausea, vomiting, diarrhea.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Distillates, petroleum, hydrotreated light paraffinic (64742-55-8)

Inhalation LC50 Rat 3900 mg/m³ 4 h

Petroleum distillates, solvent dewaxed heavy paraffinic (64742-65-0)

Oral LD50 Rat >15000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred)

Inhalation LC50 Rat >2400 mg/m³ 4 h (no deaths occurred)

PROPRIETARY ADDITIVES (64741-88-4)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat >5530 mg/m³ 4 h (no deaths occurred)

PROPRIETARY ADDITIVES (68511-50-2)

Oral LD50 Rat 5700 mg/kg; Inhalation LC50 Rat >0.39 mg/L 4 h (no deaths occurred)

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Inhalation - Vapor	2.2749 mg/L
Oral	> 2000 mg/kg

Immediate Effects

Toxic if inhaled.

Delayed Effects

May cause cancer.

Irritation/Corrosivity Data

May cause irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Product may cause cancer.

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

No information available for the product.

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

Specific Target Organ Toxicity - Single Exposure

No information on significant adverse effects.

Specific Target Organ Toxicity - Repeated Exposure

No information on significant adverse effects.

Aspiration hazard

Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Distillates, petroleum, hydrotreated light paraffinic	64742-55-8
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
PROPRIETARY ADDITIVES	64741-88-4
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
PROPRIETARY ADDITIVES	68511-50-2
Fish:	LC50 96 h Pimephales promelas 250 - 500 mg/L [static]; LC50 96 h Pimephales promelas <1000 mg/L [semi-static]
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

Potential to bioaccumulate.

Mobility

No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transportation.

IATA Information: Not regulated for transportation.

IMDG Information: Not regulated for transportation.

TDG Information: Not regulated for transportation.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION
--

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Carcinogenicity; Acute toxicity

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8	No	Yes	No	No	No

Not listed under California Proposition 65

Canada Regulations

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

Canadian WHMIS Ingredient Disclosure List (IDL)

The components of this product are either not listed on the IDL or are present below the threshold limit listed on the IDL.

Component Analysis - Inventory

Distillates, petroleum, hydrotreated light paraffinic (64742-55-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW	VN (Draft)
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	No	Yes	Yes

Petroleum distillates, solvent dewaxed heavy paraffinic (64742-65-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW	VN (Draft)
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	Yes	Yes	Yes

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

PROPRIETARY ADDITIVES (44742-58-1)(68762-65-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW	VN (Draft)
No	No	No	No	No	No	No	No	No	No	No	No	No	No	No

PROPRIETARY ADDITIVES (64741-88-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW	VN (Draft)
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	Yes	Yes	Yes

PROPRIETARY ADDITIVES (68511-50-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW	VN (Draft)
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	No

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 3 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

2018-12: Regulatory review and update.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory

Safety Data Sheet

Material Name: Performance Plus Full Synthetic Heavy Duty SAE Manual Transmission Fluid SDS ID: 820323

(KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; NDSL – Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN NCI (Draft) - Vietnam National Chemicals Inventory (NCI) (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada) .

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.