



**Section 1 - PRODUCT AND COMPANY IDENTIFICATION**

**Product Identifier**

PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)  
80W-90, 85W-140

**Product Code**

Prefix 26

**Synonyms**

Petroleum oil; Lube oil; Petroleum hydrocarbon; Lubricant; Automotive gear oil

**Recommended Use**

For lubricating differentials and final drives of automotive equipment. If this product is used in combination with other products, refer to the Material Safety Data Sheet for those products.

**Restrictions on Use**

None known.

**FOR PRODUCT MANUFACTURED IN THE U.S.A.:**

**MANUFACTURER**

Safety-Kleen Systems, Inc.  
42 Longwater Drive  
Norwell, MA 02061-9149  
U.S.A.

**SUPPLIER (in Canada)**

Safety-Kleen Canada, Inc.  
25 Regan Road  
Brampton, Ontario, L7A 1B2  
Canada

**FOR PRODUCT MANUFACTURED IN CANADA:**

**MANUFACTURER**

Safety-Kleen Systems, Inc.  
25 Regan Road  
Brampton, Ontario, L7A 1B2  
Canada

**SUPPLIER (in the U.S.A.)**

Safety-Kleen Systems, Inc.  
42 Longwater Drive  
Norwell, MA 02061-9149  
U.S.A.

[www.safety-kleen.com](http://www.safety-kleen.com)

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

**Issue Date**

September 16, 2019

**Supersedes Issue Date**

October 25, 2018

**Original Issue Date**

October 31, 1988

**Section 2 - HAZARDS IDENTIFICATION**

**Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States**

None needed according to classification criteria.

**GHS Label Elements**

**Symbol(s)**

None needed according to classification criteria.

**Signal Word**

None needed according to classification criteria

**Hazard Statement(s)**

None needed according to classification criteria.

# Safety Data Sheet

Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)

SDS ID: 82486

## Precautionary Statement(s)

### Prevention

None needed according to classification criteria.

### Response

None needed according to classification criteria.

### Storage

None needed according to classification criteria.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Other Hazards

Repeated exposure may cause skin dryness or cracking.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-62-7	Residual oils, petroleum, solvent-dewaxed	55-88
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	5-41
Mixture	Mineral Oil	0.5-2
64742-54-7	Distillates, petroleum, hydrotreated heavy paraffinic	0.25-1.25
Proprietary	Long-chain alkyl amine	0.25 -0.75

## Section 4 - FIRST AID MEASURES

### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention if needed.

### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms/Effects

#### Acute

May cause irritation.

#### Delayed

Repeated exposure may cause skin dryness or cracking.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

# Safety Data Sheet

Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)

SDS ID: 82486

## Section 5 - FIRE FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

#### Unsuitable Extinguishing Media

Do not use high pressure water streams.

### Special Hazards Arising from the Chemical

Negligible fire hazard. Avoid friction, static electricity, and sparks.

### Hazardous Combustion Products

Burning may produce: Carbon monoxide, hydrogen sulfide, oxides of sulfur, nitrogen oxides, oxides of phosphorus, unidentified organic compound.

### Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry.

### Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

## Section 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with: Skin, eyes, clothing, shoes.

### Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

### Incompatible Materials

Avoid acids, bases, oxidizing materials, and reducing agents.

# Safety Data Sheet

Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)

SDS ID: 82486

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component Exposure Limits

ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

### Appropriate Engineering Controls

Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

### Individual Protective Measures, such as Personal Protective Equipment

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: gloves, safety glasses, and lab coat or apron.

### Eyes/Face Protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

### Skin Protection

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber (latex), polyvinyl chloride (PVC) or equivalent gloves is not recommended.

### Respiratory Protection

No respiratory protection is normally required. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits.

Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Amber liquid.	<b>Physical State</b>	Liquid
<b>Odor</b>	Petroleum odor.	<b>Color</b>	Amber
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	Not available
<b>Boiling Point Range</b>	Not available	<b>Freezing point</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition Temperature</b>	Not available	<b>Flash Point</b>	190 °C Cleveland open cup (374 °F )
<b>Lower Explosive Limit</b>	Not available	<b>Decomposition temperature</b>	Not available
<b>Upper Explosive Limit</b>	Not available	<b>Vapor Pressure</b>	<0.1 mmHg @ 68°F °C (20° C )
<b>Vapor Density (air=1)</b>	Not available	<b>Specific Gravity (water=1)</b>	0.89 (Approximate Water = 1 )

# Safety Data Sheet

Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)

SDS ID: 82486

<b>Water Solubility</b>	(Insoluble )	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	>20.5 mm <sup>2</sup> /s @ 104°F (40°C)	<b>Kinematic viscosity</b>	Not available
<b>Solubility (Other)</b>	Not available	<b>Density</b>	7.4 lb/gal (US Approximate )
<b>Physical Form</b>	Liquid	<b>Volatility</b>	(Negligible )
<b>Molecular Weight</b>	Not available	<b>OSHA Flammability Category</b>	Not flammable

## Section 10 - STABILITY AND REACTIVITY

### Reactivity

No reactivity hazard is expected.

### Chemical Stability

Stable under normal temperatures and pressures.

### Possibility of Hazardous Reactions

Will not polymerize.

### Conditions to Avoid

Avoid sparks or flame when not in use.

### Incompatible Materials

Avoid acids, bases, oxidizing materials, and reducing agents.

### Hazardous decomposition products

None under normal temperatures and pressures.

## Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

#### Inhalation

May cause respiratory tract irritation. Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation.

#### Skin Contact

May cause irritation. Repeated exposure may cause skin dryness or cracking.

#### Eye Contact

May cause irritation of the eyes. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis).

#### Ingestion

May cause throat irritation, nausea, vomiting, diarrhea.

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

#### **Residual oils, petroleum, solvent-dewaxed (64742-62-7)**

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h

#### **Lubricating oils, petroleum, hydrotreated spent (64742-58-1)**

Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >4480 mg/kg

#### **Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)**

Oral LD50 Rat >15 g/kg (no deaths occurred ); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred )

### Product Toxicity Data

# Safety Data Sheet

**Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)**

**SDS ID: 82486**

**Acute Toxicity Estimate**

Oral	> 2000 mg/kg
------	--------------

**Immediate Effects**

May cause irritation.

**Delayed Effects**

Repeated exposure may cause skin dryness or cracking.

**Irritation/Corrosivity Data**

May cause irritation.

**Respiratory Sensitization**

Based on best current information, there is no known human sensitization associated with this product.

**Dermal Sensitization**

Based on best current information, there is no known human sensitization associated with these products.

**Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Based on component information, may cause cancer.

**Germ Cell Mutagenicity**

No adverse effects expected.

**Tumorigenic Data**

No data available for this product.

**Reproductive Toxicity**

No data available for this product.

**Specific Target Organ Toxicity - Single Exposure**

No target organs identified.

**Specific Target Organ Toxicity - Repeated Exposure**

No target organs identified.

**Aspiration hazard**

Not expected to be an aspiration hazard.

**Medical Conditions Aggravated by Exposure**

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

<b>Section 12 - ECOLOGICAL INFORMATION</b>
--

**Component Analysis - Aquatic Toxicity**

<b>Residual oils, petroleum, solvent-dewaxed</b>	<b>64742-62-7</b>
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
<b>Distillates, petroleum, hydrotreated heavy paraffinic</b>	<b>64742-54-7</b>
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID

**Persistence and Degradability**

No information available for the product.

# Safety Data Sheet

Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)

SDS ID: 82486

## Bioaccumulative Potential

No information available for the product.

## Mobility

No information available for the product.

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Kleen Performance Products regarding proper recycling or disposal.

### Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

## Section 14 - TRANSPORT INFORMATION

**US DOT Information:** Not regulated for transport.

**IATA Information:** Not regulated for transport.

**IMDG Information:** Not regulated for transport.

**TDG Information:** Not regulated for transport.

### International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

## Section 15 - REGULATORY INFORMATION

### Volatile Organic Compounds (As Regulated)

Negligible; As per 40 CFR Part 51.100(s)

### Canada Regulations

#### CEPA - Priority Substances List

None of this product's components are on the list.

### Ozone Depleting Substances

None of this product's components are on the list.

### Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

### Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

### U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

### SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

No hazard categories applicable.

### U.S. State Regulations

None of this product's components are listed on the state lists from CA, MA, MN, NJ or PA.

### California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

## Component Analysis - Inventory

## Safety Data Sheet

**Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)**

**SDS ID: 82486**

### Residual oils, petroleum, solvent-dewaxed (64742-62-7)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	No	No	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	No	No	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			Yes	Yes	Yes	No	Yes	Yes

### Mineral Oil (Mixture)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
No	No	No	No	No	No	No	No	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			No	No	No	No	No	No

### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			Yes	Yes	Yes	No	Yes	Yes



## Safety Data Sheet

**Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)**

**SDS ID: 82486**

**Long-chain alkyl amine (Proprietary)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
No	No	No	No	No	No	No	No	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			No	No	No	No	No	No

### Section 16 - OTHER INFORMATION

**NFPA Ratings**

Health: 1 Fire: 1 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Summary of Changes**

Update to composition. Regulatory review and update.

**Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne - Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations

## Safety Data Sheet

**Material Name: PERFORMANCE PLUS CONVENTIONAL GEAR OIL (GL-5)**

**SDS ID: 82486**

/North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft);  
WHMIS - Workplace Hazardous Materials Information System (Canada).

### **Other Information**

#### **Disclaimer:**

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Kleen Performance Products assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplier to the user.